

OE14-408 / 408E



KONGSBERG



January 2016

UNDERWATER DIGITAL STILLS CAMERA

- **10 Megapixel resolution**
- **Real time framing video**
- **True 'on-the-fly' upload capability**
- **4,500 msw Titanium alloy housing**

The Kongsberg Maritime OE14-408 (PAL and NTSC) is a new generation digital stills colour camera with smaller diameter and higher resolution than the previous model featuring 10 Megapixel resolution and 5x optical zoom.

Each image is framed using real time video and is temporarily stored in the on-board memory (standard 16Gb). Images can be uploaded on the surface using a rapid USB 2 link or over an ad-hoc wireless network. This wireless feature reduces the frequency the camera needs to be removed from the vehicle or lander, saving the operator time and improving cable and connector reliability.

For 'on-the-fly' image transfer the dedicated underwater USB 2 interface connector is available should the host vehicle have a USB over fibre capability.

The camera is also available with an additional Ethernet interface, the OE14-408E which combines all the functionality of the standard OE14-408 while also allowing the operator to control all camera functions remotely and download captured images through the 10/100 Base-T connection as soon as they are taken.

- **Tri-state/RS232/RS485/Ethernet control configurations**
- **Achromatic doublet lens minimises aberrations and distortions**

When used with the dedicated flashgun (OE11-442) the E-TTL through lens flash metering gives accurate exposure control.

The Graphical User Interface (GUI) gives full control of the camera over RS232/RS485 and also allows the cameras framing video to be displayed on the PC.

If hardwire control is preferred then zoom, focus and shutter functions can be controlled in this way.

Remote or sequential photo trigger options are also available.

Applications

- **Marine Science**
- **Autonomous Long Term Monitoring**
- **Wet Film Resolution Equivalent**
- **High End Inspection**

TECHNICAL SPECIFICATIONS

Performance

Image Resolution	User selectable, from 10Mp (3648 x 2736) to VGA (640 x 480)
Video Resolution	Framing video 360 TVL/PH
Light Sensitivity	Manual or Automatic, ISO 80 to ISO 3200
Minimum Scene Illumination	100 mV video at 510 x 10 ⁻³ lux faceplate
Signal to Noise Ratio	>45 dB
Image Storage	16 GB internal memory, estimated image storage capacities as follows: 3648 x 2736 - RAW resolution - 1100 images 3648 x 2736 – “L” Fine resolution - 6000 images 640 x 480 - “S” Normal resolution - 123,000 images

Electrical

Scan Standard	625 lines 50 Hz PAL, 525 lines 60 Hz NTSC
Sensor Elements	1/1.7” High Density CCD Sensor, 10M Pixels
Power Input	16 - 24V dc, 450mA (max) without flashgun connected OE14-408 OE14-408E
Control and Image Upload	Single wire (tri-state), RS232, RS485 TCP/IP and DHCP compatible USB 2 10/100 Base-Tx Ethernet wiring Wi-Fi IEEE802.3 compliant

Optical

Lens	6.1 - 30.5mm (35mm format equivalent to 28 - 140mm), F2.8 - F4.5
AOV in water	Horizontal: 45° Vertical: 35° Diagonal: 55°
Iris Control	Automatic (Override available through serial control)
Focus Range	Automatic or Manual (front port to infinity)

Mechanical

	OE14-408	OE14-408E
Dimensions	Diameter: 101mm Length: 239.1mm (excl. connector)	Diameter: 101mm Length: 345mm (excl. connector)
Weight	In air 4.0Kg, in water 2.1Kg	In air 5.0Kg, in water 2.2Kg
Housing Material	Titanium alloy, grade 5 6AL/4V ASTM B3 48	Titanium alloy, grade 5 6AL/4V ASTM B3 48
Connector	Camera: 8 Pin Burton 5506-1508 Flash: 8 Pin Burton 5506-1608 USB 2 Image Upload: Micro Burton 5507-0906	Control & Download: 13 pin ‘Subconn DBH13M’ Flash: 8 Pin Burton 5506-1608

Environmental

Operating Depth	4,500 msw (other depth rated housing options available)
Temperature	Operating: -5 to 40°C, Storage: -20 to 60°C
Shock	30G peak acceleration, 25ms half sine duration, on all three axes
Vibration	10G, from 20 to 150Hz on all three axes
Electromagnetic Compatibility	BS EN 61000-6-3: 2007 Emission and BS EN 61000-6-1: 2007 Immunity

Options

1,500 msw Hard Anodised Aluminum housing.

For more information contact:

Symphotic TII Corporation

805-484-6639

customer.support@symphotic.com

Specifications subject to change without any further notice

oe14408-408E_Datasheet_US / Rev.B

KONGSBERG MARITIME

Telephone: +44 1224 226500

E-mail sales: km.camsales.uk@kongsberg.com

E-mail support: km.camsupport.uk@kongsberg.com

www.km.kongsberg.com



KONGSBERG